

reach in plant growth

Percival® model PGC-10

PGC-10 uses patented high efficiency lamp bank

applications

- Frequently used for research applications such as lighting for vascular plants to facilitate standard plant production, plant pathology research and seedling germination and development

- Many other applications exist for this product

Please compare your own requirements to the specifications listed below.


percival's IntellusUltra™ controller

- Controls temperature, lighting, humidity (optional) and CO₂ (optional)
- Single-board electronic solid-state design includes 10 key membrane keypad with LED indicators and vacuum fluorescent display
- Programs can be configured to run in real time or elapsed time
- Ramping and non-ramping program methods available for each programming mode
- Multiple programs can be linked creating complex environmental profiles
- Optional IntellusUltra Web Server allows monitoring and controlling of chamber via web browser (requires Internet Explorer 6.0+) (this option allows for remote monitoring and programming of chamber including alerts and current condition updates for up to five e-mail addresses)

Please refer to www.percival-scientific.com for additional information regarding the control system.

lighting system

- Single tier plant growth bench lit by patented lamp bank specifically designed to optimize energy efficiency by managing the heat inside the lamp bank
- Design produces a constant light irradiance throughout a chamber's temperature range
- Intensity programmable up to 1075 $\mu\text{moles/m}^2/\text{s}$ measured @ 6" from barrier, utilizing a balanced spectrum for plant growth using twin T-5 fluorescent lamps and extended life tungsten incandescent lamps 3 on/off light events



lighting system (continued)

- Lamp bank is counter-balanced for adjustable light intensity
- Two levels of programming of fluorescent lighting and one level of programming of incandescent lighting done via IntellusUltra real time controller
- Utilizing the patent pending high efficiency lamp bank results in cost savings of over \$1,750 annually (assuming lights are energized for 14 hours per day in region with electrical costs of 10 cents per KW/hr.)

cabinet construction

- Interior and exterior constructed of 22-gauge electro-zinc plated steel
- Stainless steel floor
- Perforated aluminum channel work bench
- Inner shell supported by thermal conducting insulator locking inner liner in place without a metal-to-metal bond to outer case
- Chamber floor equipped with floor drain with attached $\frac{3}{4}$ " plastic tubing
- Chamber cabinet is attached to angle frame base containing heavy duty swivel caster assembly and adjustable leveling legs to compensate for floor unevenness in the lab

PGC-10 specifications (subject to change without notice)

Temp Range with all lights on	Interior Space volume		Total Shelving Floor Area		Maximum Growing Height		Exterior Dimensions						Light Intensity 6" from lamps unless otherwise noted	Tiers
							width		depth		height			
°C	ft³	m³	ft²	m²	in	cm	in	cm	in	cm	in	cm	µmoles/m²/s	
10-44±0.5	63.1	1.8	10.1	0.9	46	116.8	71	180.3	38.5*	97.8	77.6	197	1000	1

*35.5" with door removed

reach in plant growth Percival model PGC-10

airflow/circulation

- Conditioned air moves in uniform upward direction through entire work bench through perforations in aluminum channels
- Fresh air inlet and outlet are adjustable

insulation

- Woodless construction using foam-in-place 2" [5.1 cm] thick CFC free urethane insulation foam (this is an environmentally friendly foam with global warming potential [GWP] of 0.0 and ozone depletion potential [ODP] of 0.0)

door

- One door opening 26" x 48.5" (66 cm x 123.2 cm) (magnetic gasket provides a tight seal to door frame)
- 12" x 12" (30.5 cm x 30.5 cm) observation window with a light tight cover

interior space

- 63.1 ft³ (1.8 m³) with work area of 10.1 ft² (0.9 m²) provided on one tier

finish

- Interior and exterior painted with highly reflective, environmentally friendly, high temperature baked white powder coating

refrigeration

- Self-contained air-cooled condensing unit with hot gas bypass system for continuous compressor operation, extended life and close temperature control (this continuous running condensing unit ensures precise temperature control by alternately cycling refrigerant and hot gas to coil; this also prolongs life of compressor, and eliminates risk of ice build up in coil)
- Solenoid valves have extended stem for quiet and long life operation
- Heat rejection to the ambient (standard refrigeration system) with water-cooled self-contained condensing unit = 2000 BTU/hr.
- Heat rejection to the ambient (standard refrigeration system) with air-cooled self contained condensing unit = 9100 BTU/hr.

temperature range

- 2°-44°C (±0.5°C) lights off and 10°-44°C (±0.5°C) lights on (full fresh air) within work area on horizontal plane with lights on

temperature safety limit controls

- (Experiment Protection) Adjustable high and low temperature controls, audible alarms, and visual indicators provided
- Controls shut down all power to the chamber, activating alarms (when the temperature returns to the normal range the system will automatically reset)

humidity control (optional)

- Additive control of humidity in %RH through use of ultrasonic humidifiers or spray nozzles will maintain humidity levels of up to 95% RH lights off and 75% lights on, between 15° and 30°C
- Humidifier requires distilled or de-mineralized water
- Optional dehumidification via independent coiling coil and reheat heaters will maintain humidity levels down to 40% RH between 15°C and 30°C

options (most popular)

- IntellusUltra™ Web Server (C9)
- Communications Software (C9+)
- IntellusUltra with Touchscreen and Internet capabilities (C10)
- Spray nozzle humidifier with advanced RH sensor and some dehumidification via reheat heaters (H9)
- Dehumidification via independent cooling coil with reheat heaters and spray nozzle humidifier (H8)
- Ultrasonic Humidifier with advanced RH Sensor (H11)
- Dehumidification via independent dehumidifying coil with reheat heaters and Ultrasonic Humidifier (H12)
- Ultrasonic Humidifier with Electronic RH sensor (H14)
- CO₂ enrichment package
- Self-contained water-cooled condensing unit
- Dry alarm contacts
- Dimmable lighting (closed loop with PAR light sensor) (Q22)
- Dimmable lighting (open loop control) (Q23)
- Extended temperature ranges available

See other catalog sheets or consult factory for additional accessories.

convenience receptacles

- Two convenience receptacles provided inside chamber

electrical service requirements

- 208 VAC/3 phase/60 Hz, 4 wires plus ground
- Total amp draw for standard chambers without any options is 16 amps/leg

Consult factory for electrical services when adding accessories to the chamber



Percival Scientific, Inc.
505 Research Drive • Perry, IA 50220
800.695.2743 • 515.465.9363 • Fax: 515.465.9464
www.percival-scientific.com